

PLASTIC STRAP SPECIFICATION

This is to certify the product supplied by us, as specified below is manufactured according to quality procedures in compliance with ISO 9001:2000 & ISO 14001:2004

| Product | Part No | Description |
|---------------------|----------------|-------------|
| TENAX (FLAT) | 0670265 | 2040 |

CHARACTERISTICS:

Chemical: Polyester Based Plastic Strap

STRAP DETAILS:

| | | | |
|----------------------------------|---------|------------|------------|
| Width (mm) | 15.62 | Max: 16.26 | Min: 14.99 |
| Gauge (mm) | 0.89 | Max: 0.94 | Min: 0.84 |
| Minimum Break Strength (Newtons) | 5800 | | |
| Target Break Strength (Newtons) | 6300 | | |
| Elongation (%) | 10 - 15 | | |
| Grammes Per Metre | 18.44 | | |

COIL DETAILS

| | |
|--|----------|
| Coil Type | STANDARD |
| Inside Diameter (mm) | 406 |
| Outside Diameter (mm) | 610 |
| Width (mm) | 153 |
| Approx Weight (kg) excluding packaging | 24 |
| Metres / Coil | 1300 |

PALLET DETAILS

| | |
|-------------------------------------|--------------------------------|
| Pallet Dimensions (mm) | 1200 x 1200 x approx 1090 high |
| Coils / Pallet | 24 |
| Approx Gross Weight per Pallet (kg) | 634 |

QC Dept

 Signed..... Date 16th July 2007

.....